



SLM-Machine-Room-Less Technical Specification

450kg-2000kg, Centre Opening Doors

Load (kg)	Persons	Speed (m/s)	Cabin size W×D×H(mm)	Shaft size W×D(mm)	Door size W×H(mm)	Pit (mm)	Overhead (mm)
450	6	1.0	1000×1250×2350	1800×1600	800×2100	1400	3650
		1.5				1500	3750
		1.6				1500	3750
		1.75				1500	3800
630	8	1.0	1100×1400×2350	1800×1750	800×2100	1500	3650
		1.5				1500	3750
		1.6				1500	3750
		1.75				1500	3800
800	10	1.0	1200×1500×2350	1850×1850	800×2100	1500	4000
		1.5				1500	4200
		1.6	1350×1400×2350	1850×1850	800×2100	1500	4200
		1.75				1500	4300
900	12	1.0	1300×1600×2350	1950×1950	800×2100	1500	4000
		1.5				1500	4200
		1.6				1500	4200
		1.75				1500	4300
1000	13	1.0	1100×2100×2350	2100×2450	900×2100	1500	4000
			1300×1700×2350	2100×2050			
			1400×1600×2350	2100×1950			
			1450×1550×2350	2150×1900			
			1600×1400×2350	2300×1850			
		1.5	1100×2100×2350	2100×2450			
			1300×1700×2350	2100×2050			
			1400×1600×2350	2100×1950			
			1450×1550×2350	2150×1900			
			1600×1400×2350	2300×1850			
	1.6	1100×2100×2350	2100×2450				
		1300×1700×2350	2100×2050				
		1400×1600×2350	2100×1950				
		1450×1550×2350	2150×1900				
		1600×1400×2350	2300×1850				
	1.75	1100×2100×2350	2100×2450				
		1300×1700×2350	2100×2050				
		1400×1600×2350	2100×1950				
		1450×1550×2350	2150×1900				
		1600×1400×2350	2300×1850				
1150	15	1.0	1500×1700×2350	2250×2050	1000×2100	1500	4100
		1.6				1600	4300
		1.75				1600	4300
		2.0				1800	4600
1250	16	1.0	1500×1900×2350	2250×2250	1000×2100	1500	4200
		1.6			1600	4400	
		1.75			1600	4400	
		2.0			1800	4600	
1350	18	1.0	1500×2000×2350	2250×2350	1000×2100	1500	4200
		1.6			1600	4400	
		1.75			1600	4400	
		2.0			1800	4600	
1600	21	1.0	1600×2100×2350	2400×2500	1100×2100	1500	4300
		1.6				1800	4500
		1.75				1800	4500
		2.0				2200	4600
		2.5				2800	4800
		3.0				3000	4800
2000	26	1.0	1800×2200×2350	2750×2600	1200×2100	1500	4300
		1.6				1800	4600
		1.75				1800	4600
		2.0				2200	4800

SLM-Machine-Room-Less Technical Specification

450kg-2000kg, Side Opening Doors

Load (kg)	Persons	Speed (m/s)	Cabin size W×D×H(mm)	Shaft size W×D(mm)	Door size W×H(mm)	Pit (mm)	Overhead (mm)
450	6	1.0	1000×1250×2350	1600×1650	800×2100	1400	3650
		1.5				1500	3750
		1.6				1500	3750
		1.75				1500	3800
630	8	1.0	1100×1400×2350	1700×1800	900×2100	1500	3650
		1.5				1500	3750
		1.6				1500	3750
		1.75				1500	3800
800	10	1.0	1200×1500×2350	1850×1900	900×2100	1500	4000
		1.5				1500	4200
		1.6	1350×1400×2350	1850×1900	900×2100	1500	4200
		1.75				1500	4300
900	12	1.0	1300×1600×2350	1950×2000	900×2100	1500	4000
		1.5				1500	4200
		1.6				1500	4200
		1.75				1500	4300
1000	13	1.0	1100×2100×2350	1850×2500	900×2100	1500	4000
			1300×1700×2350	1950×2100	900×2100		
			1400×1600×2350	2050×2000	900×2100		
			1450×1550×2350	2100×1900	900×2100		
			1600×1400×2350	2250×1800	1000×2100		
		1.5	1100×2100×2350	1850×2500	900×2100		
			1300×1700×2350	1950×2100	900×2100		
			1400×1600×2350	2050×2000	900×2100		
			1450×1550×2350	2100×1900	900×2100		
			1600×1400×2350	2250×1800	1000×2100		
	1.6	1100×2100×2350	1850×2500	900×2100			
		1300×1700×2350	1950×2100	900×2100			
		1400×1600×2350	2050×2000	900×2100			
		1450×1550×2350	2100×1900	900×2100			
		1600×1400×2350	2250×1800	1000×2100			
	1.75	1100×2100×2350	1850×2500	900×2100			
		1300×1700×2350	1950×2100	900×2100			
		1400×1600×2350	2050×2000	900×2100			
		1450×1550×2350	2100×1900	900×2100			
		1600×1400×2350	2250×1800	1000×2100			
1150	15	1.0	1500×1700×2350	2200×2100	1000×2100	1500	4100
		1.6				1600	4300
		1.75				1600	4300
		2.0				1800	4600
1250	16	1.0	1500×1900×2350	2200×2300	1000×2100	1500	4200
		1.6			1600	4400	
		1.75			1600	4400	
		2.0			1800	4600	
1350	18	1.0	1500×2000×2350	2200×2400	1000×2100	1500	4200
		1.6			1600	4400	
		1.75			1600	4400	
		2.0			1800	4600	
1600	21	1.0	1600×2100×2350	2300×2500	1300×2100	1500	4300
		1.6				1800	4500
		1.75				1800	4500
		2.0				2200	4600
		2.5				2800	4800
		3.0				3000	4800
2000	26	1.0	1800×2200×2350	2600×2600	1300×2100	1500	4300
		1.6				1800	4600
		1.75				1800	4600
		2.0				2200	4800

